

NCA

Threaded Stud

RH Thread	LH Thread	Cable Diameter	Thread B UN-3A UNF-3a	A	As	C	D	L	Ls	N	P	R	S	W	Y	Lbs/pc
MS21259-2RH	MS21259-2LH	1/16	6-40	.160	.138	.121	.188	2.473	2.65	0.078	1.042	0.063	0.969	1.174	1.045	0.01
MS21259-3RH	MS21259-3LH	3/32	10-32	.218	.190	.169	.250	2.879	3.00	0.109	1.261	0.063	1.188	1.411	1.204	0.0225
MS21259-4RH	MS21259-4LH	1/8	1/4-28	.250	.219	.226	.313	3.333	3.59	0.141	1.511	0.063	1.438	1.682	1.376	0.0375
MS21259-5RH	MS21259-5LH	5/32	1/4-28	.297	.250	.226	.313	3.627	3.97	0.172	1.761	0.063	1.688	1.958	1.376	0.0475
MS21259-6RH	MS21259-6LH	3/16	5/16-24	.359	.313	.285	.375	4.002	4.17	0.203	2.011	0.098	1.938	2.237	1.458	0.08
MS21259-7RH	MS21259-7LH	7/32	3/8-24	.427	.375	.347	.438	4.516	4.81	0.234	2.261	0.098	2.188	2.518	1.625	0.12
MS21259-8RH	MS21259-8LH	1/4	3/8-24	.494	.438	.347	.500	4.937	5.24	0.265	2.511	0.098	2.438	2.784	1.75	0.165

